



NEXOPART UFA

Ultrasonic frequency variation for sieve support.

NEXOPART

simplicity for your lab

NEXOPART UFA

Ultrasonic frequency variation for sieve support.

With the NEXOPART UFA you have an important tool in your hand if you want to analyze your fine bulk material e.g. fine powders with critical separation cuts of $\leq 300 \mu\text{m}$ successfully via a vibrating sieve instrument. By using the UFA unit the sieve mesh is stimulated with a continuously varying ultrasonic frequency. The high-frequency vibrations that are generated reduce the frictional resistance between particles and sieve cloth. Sieve support with the NEXOPART UFA significantly speeds up the process of reaching the end point of sieving. For some bulk materials, sieving with vibratory test sieve shakers is only now possible correctly for the first time. The special feature of this process is the frequency variation, which does not require any complex tuning of the mechanics to be stimulated (test sieves) - in contrast to the usual resonance methods.

Advantages of the NEXOPART UFA:

- increased sieve throughput of bulk materials $\leq 300 \mu\text{m}$
- clogging tendency is minimized and destruction of agglomerates is promoted
- sieving capacity is increased and sieving time is shortened
- permanent cleaning effect of the sieve cloth with low mechanical load on the sieve bottom
- parallel processing of several test sieves with only one generator (possibility to connect two converters, twin operation)

TECHNICAL SPECIFICATIONS AT A GLANCE.

	AGS 35-100	DGS 35-50-S
Clamping ring:	$\varnothing 50 \text{ mm}, 76,2 \text{ mm}, 200 \text{ mm}, 203 \text{ mm}, 300 \text{ mm}, 305 \text{ mm}, 315 \text{ mm}, 350 \text{ mm}, 400 \text{ mm}, 450 \text{ mm}$	$\varnothing 50 \text{ mm}, 76,2 \text{ mm}, 200 \text{ mm}, 203 \text{ mm}, 300 \text{ mm}, 305 \text{ mm}, 315 \text{ mm}, 350 \text{ mm}, 400 \text{ mm}, 450 \text{ mm}$
Converter:	C35-LP1 including connection cable	C35-LP1 including connection cable or C35-SD8 including connection cable
Generator type:	analog	digital
Ultrasonic power:	20-100 W (adjustable)	50 W max. (adjustable)
Operating modes:	continuous / pulsing	continuous / pulsing
Protection class:	IP 65	IP 65
Weight:	3,3 kg	3,6 kg



Clamping ring and converter before using the test sieve to be stimulated



Analog generator for stimulation of a test sieve (AGS35-100)



Digital generator for excitation of test sieves with expanded analysis and setting options with additional SweepParam software

NEXOPART GmbH & Co. KG

A Haver & Boecker and Hosokawa Alpine Company

Ennigerloher Str. 64
59302 Oelde
Germany

sales@nexopart.com
www.nexopart.com

DB 31 E 02 102025 UFA PDF NEXOPART®.

Any kind of duplication, also in extracts, only with permission.

As an innovative company, Nexopart® protects its intellectual property. NEXOPART® know-how is protected by the following intellectual property rights: Word mark NEXOPART in the protection area DE (30 2022 110 345), IR UK (W0000001740397), IR EU (T740397) and IR US (7,525,699).

Photos: Walkenhorst, supervisuell, NEXOPART

The use of the NEXOPART UFA enables the sieving of adhesive bulk materials

